

K2 POWER ES 130K

2-way component kit



Aluminum chassis new design

- Rigid, antimagnetic with exclusive design for a better excursion

K2 Power sandwich cone

- Dynamic & precise

Separated compact crossover (Tweeter 0 / +3 / - 3 dB/oct)

- Quick install and easy settings



Tweeter: 3 assembly solutions

- Factory location
- Flush
- In oriented pod

Integrated terminal

More compact

Butyl surround exclusive patent "TMD" (Tuned Mass Damper) with S/N engraved

- Better control, more neutral and linear sound

TKM "M" profile aramid fiber inverted dome tweeter

- High extension in treble
- Smooth and precision

WHAT MAKES THE DIFFERENCE

- Inverted dome "M"-shaped tweeter
- High linearity
- High SPL (for the size)

TECHNICAL CHARACTERISTICS

2-way component kit

Diameter: 5" (130mm)

Voice coil diameter: 1" (25mm)

Voice coil height: 0¹/₂" (12mm)

Motor: Magnet

Tweeter: TKM ["M" profile aramid fiber inverted dome]

Cone: Composite K2 Power "W" sandwich cone

Surround: Tuned Mass Damper (TMD®)

Separated crossover: 6-12/12dB (3.5kHz)

Tweeter Adjustable level: +3; 0; -3dB/oct

Max. power: 160W

Nom. power: 80W RMS

Sensitivity (2.83V/1m): 90dB

Frequency response: 65Hz- 22kHz

Impedance: 4 Ω

Accessories: Supplied grilles



Elite

"HAUTE COUTURE" SOUND



FOCAL

THE SPIRIT OF SOUND